

## Flexible COB LED Strip - High Density

**Model Number:** COB-RBL-XX (IP20) & COB-STRIP-XX (IP65)



### COLOR/CCT



- WARM WHITE 2700K:** 2700 Kelvin Temp, 290/ft lumens
- WARM WHITE:** 3000 Kelvin Temp, 305/ft lumens
- NEUTRAL WHITE:** 4000 Kelvin Temp, 320/ft lumens
- COOL WHITE:** 5000 Kelvin Temp, 425/ft lumens


### TECHNICAL PARAMETERS

<b>Voltage</b>	24VDC	<b>IP Rating</b>	IP 20 / IP65
<b>Wattage</b>	60W/5M	<b>Dimmable</b>	Yes, if used with a dimmable driver
<b>Cuttable</b>	Every 2"	<b>Product Length</b>	5M (16.25 feet), 15M (49 feet)
<b>LED Diode</b>	SMD 2110	<b>Colors Available</b>	Warm White 2700K, Warm White, Neutral White, Cool White
<b>CRI</b>	CRI > 90	<b>Kelvin Temp</b>	2700K (WW-2700K), 3000K (WW), 4000K (NW), 5000K (CW)
<b>Certificate</b>	ETL Approved		

### ITEM ID & DESCRIPTION

IP20 (5M)	IP20 (15M)	IP65 (15M)	
COB-RBL-WW-2700K	COB-RBL-WW-2700K-15	COB-STRIP-WW-2700K-15	24VDC, CCT 2700K, Warm White 2700K
COB-RBL-WW-3000K	COB-RBL-WW-3000K-15	COB-STRIP-WW-3000K-15	24VDC, CCT 3000K, Warm White
COB-RBL-NW	COB-RBL-NW-15	COB-STRIP-NW-15	24VDC, CCT 4000K, Neutral White
COB-RBL-CW	COB-RBL-CW-15	COB-STRIP-CW-15	24VDC, CCT 5000K, Cool White

### CONNECTORS



1. WC-COB-8
2. WC-COB-10
3. JC-COB-8
4. JC-COB-10
5. CC-COB-8
6. CC-COB-10
7. WC-COB-IP65-N
8. JC-COB-IP65-N

PCB to Wire Connector, 6" Wire, for 8mm PCB  
 PCB to Wire Connector, 6" Wire, for 10mm PCB  
 Splice Connector for 8mm PCB  
 Splice Connector for 10mm PCB  
 Corner Connector, 6" Wire, for 8mm PCB  
 Corner Connector, 6" Wire, for 10mm PCB  
 PCB to Wire Connector, No Wire, for IP65 10mm PCB  
 Splice Connector, No Wire, for IP65 10mm PCB

### DIMMABLE MAGNETIC LED DRIVERS

- FL-60W-24V-LED-DIM1
- FL-100W-24V-LED-DIM1
- FL-150W-24V-LED-DIM1
- FL-200W-24V-LED-DIM1
- FL-300W-24V-LED-DIM1
- FL-600W-24V-LED-DIM1

### DIMMABLE ELECTRONIC LED DRIVERS

- FL-60W-24V-LED-DIM4
- FL-120W-24V-LED-DIM4
- FL-200W-24V-LED-DIM4
- FL-300W-24V-LED-DIM4