



## Flexible COB LED Strip - High Density

**Model Number:** ETL-RBL-COB-XX (IP20) & ETL-STRIP-COB-XX (IP65)



### COLOR/CCT

	<b>WARM WHITE 2700K</b>
	2700 Kelvin Temp
	290/ft lumens
	<b>WARM WHITE</b>
	3000 Kelvin Temp
	305/ft lumens
	<b>NEUTRAL WHITE</b>
	4000 Kelvin Temp
	320/ft lumens
	<b>COOL WHITE</b>
	5000 Kelvin Temp
	425/ft lumens

### TECHNICAL PARAMETERS

<b>Voltage</b>	24VDC	<b>IP Rating</b>	IP 20 / IP65
<b>Wattage</b>	60W/5M	<b>Dimmable</b>	Yes, if used with a dimmable driver
<b>Cuttable</b>	Every 2"	<b>Product Length</b>	5M (16.25 feet), 15M (49 feet)
<b>LED Diode</b>	SMD 2110	<b>Colors Available</b>	Warm White 2700K, Warm White, Neutral White, Cool White
<b>CRI</b>	CRI > 90	<b>Kelvin Temp</b>	2700K (WW-2700K), 3000K (WW), 4000K (NW), 5000K (CW)
<b>Certificate</b>	ETL Approved		

### ITEM ID & DESCRIPTION

IP20 (5M)	IP20 (15M)	IP65 (15M)	
ETL-RBL-COB-WW-2700K	ETL-RBL-COB-WW-2700K-15	ETL-STRIP-COB-WW-2700K-15	24VDC, CCT 2700K, Warm White 2700K
ETL-RBL-COB-WW	ETL-RBL-COB-WW-15	ETL-STRIP-COB-WW-15	24VDC, CCT 3000K, Warm White
ETL-RBL-COB-NW	ETL-RBL-COB-NW-15	ETL-STRIP-COB-NW-15	24VDC, CCT 4000K, Neutral White
ETL-RBL-COB-CW	ETL-RBL-COB-CW-15	ETL-STRIP-COB-CW-15	24VDC, CCT 5000K, Cool White

### DIMMABLE MAGNETIC LED DRIVERS

- FL-60W-24V-LED-DIM1
- FL-100W-24V-LED-DIM1
- FL-150W-24V-LED-DIM1
- FL-200W-24V-LED-DIM1
- FL-300W-24V-LED-DIM1
- FL-600W-24V-LED-DIM1

### DIMMABLE ELECTRONIC LED DRIVERS

- FL-60W-24V-LED-DIM3
- FL-100W-24V-LED-DIM3
- FL-150W-24V-LED-DIM3
- FL-200W-24V-LED-DIM3
- FL-300W-24V-LED-DIM3